




Nexus

DESCRIPTION Paver TEXTURE HD² Smooth

PALLET OVERVIEW



Specifications per pallet	Imperial	Metric
Cubing	ft	7.86 m ²
Approx. Weight	3 543 lbs	1 607 kg
Number of rows	8	
Coverage per row	10.57 ft ²	0.98m ²
	7.98 ft/row	2.43 m/row
	3.98 ft/row	1.21 m/row


Unit dimensions	in	mm	Units/pallet
Height	3 ⁹ / ₁₆	90	24 units
Width	15 ⁷ / ₈	404	
Length	31 ¹⁵ / ₁₆	811	




PHYSICAL AND CHEMICAL PROPERTIES

SiO ₂ %	96 to 99%
Iron (Fe2O ₃)%	0.56%
Alumina (Al ₂ O ₃)%	NIL
Lime (CaO)%	NIL
Magnesia (MgO)%	NIL
Loss On Ignition (LOI)%	0.38
Bulk Density (Test Method - ASTM - C97/C 97M-09):	2471.53
Bulk Specific Gravity (Test Method- ASTM C97/c 97M-09):	2.5
Water Absorption (Test Method- ASTM C97/C 97M-09):	1.6
Abrasion Resistance (Test Method- ASTM C 241/C 241M-09):	46.61
Resistance to salt Crystallization (Test method-EN12370:1999) (Mass Gain (%)):	0.68
Durability of Natural Building Stones (Test method IS 1126:1974) (Change in mass loss or Gain):	(-)0.125
Modulus of Rupture (Test Method - ASTM C99/C 99 M - 09), Average Value:	18.72
Compressive Strength, Mpa (Test Method -ASTM C170/C 170M-09):	98.82
Flexural Strength, Mpa (Test Method - ASTM C880/C 880M - 09):	16.63


01 | Linear pattern




02 | Linear pattern



03 | Linear pattern



04 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Terra Linea Terra Save

