




Evercrest

DESCRIPTION Paver TEXTURE Smooth

PALLET OVERVIEW



Specifications per pallet	Imperial	Metric
Cubing	ft	7.37 m ²
Approx. Weight	2 952 lbs	1 339 kg
Number of rows	8	
Coverage per row	9.92 ft ²	0.92 m ²
Linear coverage per row	12.60 lin. ft	3.84 lin. m
	50.39 lin. ft	15.36 lin. m



A




Unit dimensions	in	mm	Units/pallet
Height	3 1/8	80	512 units
Width	2 3/4	60	
Length	9 7/16	240	


PHYSICAL AND CHEMICAL PROPERTIES

SiO ₂ %	96 to 99%
Iron (Fe ₂ O ₃)%	0.56%
Alumina (Al ₂ O ₃)%	NIL
Lime (CaO)%	NIL
Magnesia (MgO)%	NIL
Loss On Ignition (LOI)%	0.38
Bulk Density (Test Method - ASTM - C97/C 97M-09):	247153
Bulk Specific Gravity (Test Method- ASTM C97/c 97M-09):	2.5
Water Absorption (Test Method- ASTM C97/C 97M-09):	1.6
Abrasion Resistance (Test Method- ASTM C 241/C 241M-09):	46.61
Resistance to salt Crystallization (Test method-EN12370:1999) (Mass Gain (%)):	0.68
Durability of Natural Building Stones (Test method IS 1126:1974) (Change in mass loss or Gain):	(-)0.125
Modulus of Rupture (Test Method - ASTM C99/C 99 M - 09), Average Value:	18.72
Compressive Strength, Mpa (Test Method -ASTM C170/C 170M-09):	98.82
Flexural Strength, Mpa (Test Method - ASTM C880/C 880M - 09):	16.63


01 | Linear pattern




02 | Linear pattern




03 | Linear pattern



04 | Herringbone pattern



05 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Terra Linea

Terra Save

