





Wavecrest

DESCRIPTION: Paver TEXTURE: Smooth

PALLET OVERVIEW



Specifications per pallet		Imperial	Metric
Cubing		78.39 ft²	7.28 m ²
Approx. Weight		2 245 lbs	1 018 kg
Number of rows		7	
Coverage per row		11.20 ft ²	1.04 m ²
Linear coverage per row	Depth	13.39 lin. ft	4.08 lin. m
	Length	6.69 lin. ft	2.04 lin. m



Unit dimensions	in	mm	Units/pallet
Height	3 15/16	100	56 units
Width	10 1/16	255	
Length	20 1/16	510	

PHYSICAL AND CHEMICAL PROPERTIES


SiO ₂ %	96 to 99%
Iron (Fe2O ₃)%	0.56%
Alumina (Al ₂ O ₃)%	NIL
Lime (CaO)%	NIL
Magnesia (MgO)%	NIL
Loss On Ignition (LOI)%	0.38
Bulk Density (Test Method - ASTM - C97/C 97M-09):	2471.53
Bulk Specific Gravity (Test Method - ASTM C97/C 97M-09):	2.5
Water Absorption (Test Method - ASTM C97/C 97M-09):	1.6
Abrasion Resistance (Test Method - ASTM C 241/C 241M-09):	46.61
Resistance to salt Crystallization (Test method-EN12370:1999) (Mass Gain (%)):	0.68
Durability of Natural Building Stones (Test method IS 1126:1974) (Change in mass loss or Gain):	(-)0.125
Modulus of Rupture (Test Method - ASTM C99/C 99 M - 09), Average Value:	18.72
Compressive Strength, Mpa (Test Method -ASTM C170/C 170M-09):	98.82
Flexural Strength, Mpa (Test Method - ASTM C880/C 880M - 09):	16.63

JOINT WIDTH: 1 5/8" (41 mm)
% OF SURFACE OPENING: 38 %
INFILTRATION RATE: 2 395 in./hr
 (60 842 mm/hr)


WINTER CONDITIONS

De-icing salts should never be used on grass as salt will damage it. The snowblower blade should be set to leave a 3/4 to 1 1/2 in. (2 to 4 cm) tamped snow cover to protect the grass from extreme cold and prevent it from being torn off during snow removal.


01 | Linear pattern




02 | Linear pattern



03 | Herringbone pattern



04 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Terra Save Terra Linea

